| D | |


Documentation 🔻

Resources ♥ My Ac

My Account ♥ Customer Support ♥

Home > Products > By Type > PCB Connectors > Product Feature Selector > Product Details

280610-1 Product Details



280610-1

TE Part Number: 280610-1

Active

■ Add to Part List

.156 Inch AMPMODU .031 X .062 Mod l

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Header
- Vertical Mount Angle
- Tin (150) Contact Mating Area Plating Material
- Not Keyed
- Number of Positions = 4

<u>View all Features</u> | <u>Find Similar</u> Products

Live Product Chat

Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product
- Request Samples

 NEW!

Documentation & Additional Information

Product Drawings:

 AMP MODU MODI STRAIGHT VERSION POST SUPPORT ASSY (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version R)
- 3D Model (IGES, Version R)
- 3D Model (STEP, Version R)

Additional Information:

Product Line Information

Related Products:

Tooling

<u>List all Documents</u>

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Header
- Mount Angle = Vertical
- Keyed = No
- Number of Positions = 4

Mechanical Attachment:

• Mating Post Length (mm [in]) = 10.00 [0.394]

Termination Related Features:

Termination End Plating = Tin (150)

Body Related Features:

- Number of Rows = Single
- Centerline (mm [in]) = 3.96 [0.156]

Contact Related Features:

- Contact Mating Area Plating Material = Tin (150)
- Contact Material = Phosphor Bronze

Housing Related Features:

- Housing Material = Polycarbonate
- Housing Color = Green
- Housing Flammability Rating = UL 94V-1

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• Terminate To = Printed Circuit Board

Other:

Brand = AMP