



What can we help you find?



Products

Industries

Resources

About TE

My Account

Innovation

Support Center

Home > Products > Modular Jacks & Plugs > Product Feature Selector > Product Details

5557566-1 Product Details





Pricing & Availability Search for Tooling

Product Feature Selector

Contact Us About This Product





5557566-1

TE Internal Number: 5557566-1 🥒 Active

PCB Mounted Jacks - Single Port, Multi-port and Stacked

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Preloaded
- Multiple Port Configuration
- 1 x 8 Jack Configuration
- Jack Type = RJ45

View all Features

















Documentation & Additional Information

Product Drawings:

MODULAR JACK ASSEMBLY, EIGHT PORT,8 POSITION, RIGHT ANGLE (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

High Performance Modular Plugs & Jacks, PCB Mounted (PDF, English)

Application Specifications:

Modular Jacks (PDF, English)

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Related Products:

Tooling



Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Jack Type = RJ45
- PCB Mounting Orientation = Side Entry (Right Angle)
- PCB Mount Style = Through Hole
- Termination Method to PC Board = Solder
- Performance Category = Cat 3
- LED = Without
- Grounding Options = Without
- Panel Stops = Without
- Keyed = No.
- Profile = Standard
- Color = Black

Mechanical Attachment:

Panel Mount Retention = Without

Electrical Characteristics:

Shielded = No.

Termination Features:

Solder Tail Contact Plating = Tin over Nickel

Dimensions:

PCB Tail Length (mm [in]) = 3.56 [0.140]

Body Features:

- Inverted Jack Face = No
- Number of Contacts Loaded, RJ45 (8 Positions) = 8

Contact Features:

List all Documents

- Contact Plating, Mating Area, Material = Gold (50)
- Contact Base Material = Phosphor Bronze

Housing Features:

- Housing Material = High Temperature Nylon
- UL Flammability Rating = UL 94V-0

Configuration Features:

- Preloaded = Yes
- Port Configuration = Multiple
- Jack Configuration = 1 x 8
- Number of Positions = 8 Number of Contacts Loaded = 8

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Features:

- Packaging Method = Tray
- Packaging Quantity = 10

Product Availability:

Region = Asia, North America

Other:

- Brand = AMP
- Comment = On any modular jack, Terminal No. 1 is the terminal to the extreme left as you face the jack opening, tab notch down.

Corporate Information

About TE Investors News Room Supplier Portal Quick Links Distributor Inventory Product Cross Reference Documents & Drawings Product Compliance Support Center

Customer Support Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

Keep Me Informed













Careers

Site Map