, solder terminal, insulated, 3-pole, Audio Plug/Sockets, 3.5 mm



See below:

Approvals and Compliances

Description

- Solder terminal : for cable mounting
- Audio entrances and exits
- Data and Signal transfer
- Audio Plug: 3-pole, insulated, angled

D,	٠fa:		ces
ne	:IEI	еп	CES

Alternative: Housing shielded 4832.1300

Weblinks

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product

Tech	nical	Data

Diameter	3.5 mm		
Number of Poles	3-pole		
Ratings DC	0.5 A / 30 VDC		
Ratings AC	0.5 A / 30 VAC		
Dielectric Strength	500 VDC		
Insulation Resistance	> 100 MΩ @ 500 VDC		

Allowable Operation Tempe-	-20°C to 70°C
rature	
Terminal	solder terminal nickel-plated
Housings	insulated
Style	angled
Lifetime	5000 Insertions

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals


SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.


Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
50	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimensions [mm]





Cable diameter max. 4.0 mm

All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Audio Plug/Sockets	3.5	3-pole	solder terminal	4832.1320

 $A \textit{vailability} for \textit{all} \textit{products} \textit{can} \textit{be} \textit{searched} \textit{real-time:} \textit{https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER} \textit{all} \textit{products} \textit{can} \textit{be} \textit{searched} \textit{real-time:} \textit{https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER} \textit{all} \textit{products} \textit{can} \textit{be} \textit{searched} \textit{real-time:} \textit{https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER} \textit{all} \textit{products} \textit{can} \textit{be} \textit{searched} \textit{real-time:} \textit{https://www.schurter.com/en/Stock-Check-SCHURTER} \textit{all} \textit{can} \textit{can} \textit{be} \textit{can} \textit{$

_				
ഥവ	$\alpha \mathbf{v} \circ$	ainc	a unit	
гα	CNO	ullic	4 WI II L	

100 Pcs

Mating Outlets/Connectors

Category / Description

Audio Plug/Sockets Overview complete



, solder terminal, screened, 3-pole, Audio Plug/Sockets, 3.5 mm	4832.2300	
, PCB terminals, screened, 3-pole, Audio Plug/Sockets, 3.5 mm	4832.2320	
, PCB terminals, insulated, 3-pole, Audio Plug/Sockets, 3.5 mm	4832.2330	
, solder terminal, insulated, 3-pole, Audio Plug/Sockets, 3.5 mm	4832.3300	
Audio Plug/Sockets further types to 4832.1320		

information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each

product selected for their own applications.