Fuseholder Open Design, 5 x 20 mm, Solder, Cover





Screw/- Rivet mounting from front side Solder terminal Open fuseholder 5 x 20 mm bar Solder terminal

600 VAC/DC · 10 A (UL/CSA)

Description

- Optional covers, see accessories
- 10 piece strip manually separable

Technical Data

lechnical Data	
Fuse-Link	5 x 20 mm
Attachment	Screw or Rivet
Terminal	Solder
Rated Voltage	600 VAC/DC
Rated current	10A (UL/CSA)
Admissible Ambient Air Temp.	-40 °C to 85 °C
Climatic Category	40/085/21 acc. to IEC 60068-1
Material: Socket	Thermoset, black, UL 94V-0
Material: Cover	Thermoplastic Transparent UL 94V-0
Material: Terminals	Nickel-Silver
Unit Weight	3.62 g
Storage Conditions	0°C to 60°C, max. 70% r.h.
Product Marking	I , Rated Voltage, Rated current, Certification marks

Soldering Methods	Iron
	Soldering Profile
Solderability	350 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 2
Resistance to Soldering Heat	350 °C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 2
Contact Resistance	≤ 10 mΩ at 100 mA acc. to IEC 60127-6
Dielectric Strength	> 3kV between life parts (50Hz: 1 min)
Impulse Withstand Voltage	> 4 kV between life parts
Insulation Resistance	> 10 MΩ between life parts (500 VDC: 1 min)

pdf data sheet, html datasheet, General Product Information, Packaging

details, Distributor-Stock-Check, Accessories, Detailed request for

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

See below:

Weblinks

product. Microsite

Approvals and Compliances

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: UH

Approval Logo	Certificates	Certification Body	Description	
c FL us	UL Approvals	UL	UL File Number: E39328	
Product standards	6			
Product standards that are referenced				
Organization	Design	Standard	Description	
(Ų)	Designed according to	UL 4248-1	Fuseholder general requirements	
GE Group	Designed according to	CSA C22.2 no. 4248.1	Fuseholder general requirements	

Application standards


Application standards where the product can be used

Organization	Design	Standard	Description
IEC.	Designed for applications acc.	IEC/UL 62368-1	IEC 62368-1 includes the basic requirements for safety of audio, video, information technology and office equipment.
Compliances			


المك مالك

The product complies with following Guide Lines				
Identification	Details	Initiator	Description	
CE		SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.	
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863	
(China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.	
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.	

Dimension [mm]




47 mm



Variant 0031.5001

Derating Curves


without Cover




with cover

Admissible Power Acceptance in

Variant 0031.5010



All Variants



Accessories

Description



Cover OG, UHB, UH

Cover for Holder OG (Clip) 5x20, OG (Halter) 5x20, UH, UHB