

GLF1608T220M

Applications

Commercial Grade

Feature

Wire Wound

Shield

Magnetic Shield

No Directivity

Ferrite Core

Series

GLF Series / GLF1608 Type


Status

OBSL(Recommended Alternate Part Number:MLZ1608M220WT000)

Discontinue Issue Date: Apr.27, 2011

Last Purchase Order Date: Jun.30, 2012

Last Shipment Date: Sep.30, 2012











Size	
Length(L)	1.60mm Nom.
Width(W)	0.80mm Nom.
Thickness(T)	0.80mm +/-0.20mm
Recommended Land Pattern (A)	0.70mm Nom.
Recommended Land Pattern (B)	0.70mm Nom.
Recommended Land Pattern (C)	0.70mm Nom.

Electrical Characteristics		
Inductance	22uH +/-20% at 2.52MHz	
Rated Current (L Change) [Max.]	60mA (30% Down)	
Rated Current (Temperature Rise) [Max.]	100mA (20degC Rise)	
DC Resistance [Nom.]	3Ω	
DC Resistance [Max.]	3.9Ω	

Other		
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 105degC	
Soldering Method	Flow, Reflow, Iron Soldering	
AEC Q200	No	
Packing	Punched (Paper)Taping [180mm Reel]	
Package Quantity	4000Pcs Min.	
Weight	0.005g	


[•]This PDF document was created based on the data listed on the TDK Corporation website.


[•]All specifications are subject to change without notice.



GLF1608T220M

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)






GLF1608T220M

GLF1608T220M





GLF1608T220M

GLF1608T220M

[•]This PDF document was created based on the data listed on the TDK Corporation website.


[•]All specifications are subject to change without notice.



GLF1608T220M

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)





GLF1608T220M(Amb. Temp. = 20degc)

GLF1608T220M(DC = 0A)

GLF1608T220M(DC = 0.03A)

Temperature Rise by DC		
	no data available	

[•]This PDF document was created based on the data listed on the TDK Corporation website.

[•]All specifications are subject to change without notice.