SIEMENS

Data sheet US2:52PL4JB

PILOT LIGHT,XFR 480V,WHITE,PLAS PILOT LIGHT,XFR 480V,WHITE,PLAS



product brand name	Siemens Pilot Devices	
Design of the product	Complete Unit, Round	
Enclosure:		
Number of command points	1	
Delivery state		
● as a kit	No	
Actuator:		
Design of the operating mechanism	Indicator Light	
Product expansion optional Light source	Yes	
Color		
 of the actuating element 	White	
Material of the actuating element	plastic	
Shape of the actuating element	Concentric rings	
Front ring:		
Product component front ring	Yes	
Design of the front ring	standard	
Material of the front ring	metal	
Color of the front ring	chrome	

Holder:		
Material of the holder	metal	
Contact block/ lampholder:		
Mounting type	BA 9s, with incandescent lamp	
Number of lampholders	1	
2: 1		
Display: Number of LED modules	0	
Number of LED modules	0	
General technical data:		
Product component		
 lamp transformer 	Yes	
• Light source	Yes	
Surge voltage resistance rated value	4 kV	
Protection class IP	IP66	
• of the terminal	IP20	
Degree of pollution	1	
Vibration resistance		
• acc. to IEC 60068-2-6	0 2000 Hz, 1.52 mm displacement (peak-to-peak) max./ 10g	
	max.	
Mechanical service life (switching cycles)		
• typical	5	
Supply voltage:		
Type of voltage of the supply voltage		
• of the light source	AC	
Supply voltage 1 of the light source at AC		
• at 60 Hz rated value	6 V	
Inputs/ Outputs:		
Output voltage 1 of the lamp transformer rated value	6 V	
2		
Connections/ Terminals:	garay type terminals	
Type of electrical connection	screw-type terminals	
of modules and accessories Tight arise to access liberia.	screw-type terminals	
Tightening torque [lbf·in]	0 0 lbf:-	
with screw-type terminals	8 8 lbf·in	
Lamp:		
Lamp: Type of light source	Incandescent	
Type of light source	Incandescent	
Type of light source Color of the light source	Incandescent	
Type of light source Color of the light source Safety related data:	Incandescent	
Type of light source Color of the light source Safety related data: Protection against electrical shock	Incandescent	

-35 ... +70 °C during operation -40 ... +85 °C • during storage

Installation/ mounting/ dimensions:	
Mounting type	
 of modules and accessories 	screw-mounting
Shape of the installation opening	round

Certificates/approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PL4JB

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PL4JB

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/US2:52PL4JB

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PL4JB&lang=en

last modified: 13.02.2016