




Solutions

Agriculture

Agriculture

Solutions for



Tractors and agricultural machinery

Silos

Feed distribution systems

Irrigation

ABOUT CARLO GAVAZZI

Carlo Gavazzi Automation is an international group active in designing, manufacturing and marketing electronic equipment targeted at the global markets of industrial and building automation.

Our history is full of firsts and our products are installed in a huge number of applications all over the world. With more than 80 years of successful operation, our experience is unparalleled.

We have our headquarters in Europe and numerous offices around the world.

Our R&D competence centres and production sites are located in Denmark, Italy, Lithuania, Malta and the People's Republic of China.

We operate worldwide through 22 of our own sales companies and also selected representatives in more than 65 countries, from the United States in the West to the Pacific Rim in the East.

Our core competence in automation spans three product lines: Sensors, Switches and Controls.

Our wide array of products includes sensors, monitoring relays, timers, energy management system, solid state relays, safety devices and fieldbus systems.

We focus our expertise on offering state-of-the-art product solutions in selected market segments.

Our customers include original equipment manufacturers of packaging machines, plastic-injection moulding machines, food and beverage production machines, conveying and material handling equipment, door and entrance control systems, lifts and escalators, as well as heating, ventilation and air-conditioning devices.



DESIGNED TO MEET MARKET REQUIREMENTS

Agricultural mechanization has brought major changes to agriculture and eased the burden on farm workers. Advances in tractor technology have made tractors more versatile and suitable for a wider range of farming tasks.

Machinery for ploughing and cultivation have contributed to boosting production. Special machinery is used to plant seeds and apply fertilizer through mulch at the correct depth. In irrigation, technologies such as micro sprinklers or drip irrigation that save water and consume less power are the environmentally friendly solutions for now and the future.

The global agricultural machinery industry provides more support to smallholders and other farmers with equipment designs and models that suit their needs and those of service providers.

Carlo Gavazzi offers, among other things, a wide range of sensors to measure speed and rotational direction of wheels in farm tractors, harvesting machines etc.

Carlo Gavazzi's capacitive sensors are widely used for level measurements of seed, fodder and liquids in silos and in animal feeding machinery. Ultrasonic sensors are used mainly for level measurements of liquids (e.g. milking machinery).

Reliable irrigation systems are highly important for agricultural production. The well proven Dupline® fieldbus with its up-to-the-minute technology, has become known as an extremely user-friendly and flexible fieldbus able to transmit signals over long distances - features that make Dupline® ideal as a fieldbus for irrigation systems.

Finally – thanks to Carlo Gavazzi's wide product range – most agricultural application challenges can be met by one supplier.

Agriculture

Tractors and agricultural machinery



Inductive sensors

**ICB12
ICB18
ICB30**

Pick up sensors

PA2PK

Ultrasonic sensors

**UA18
UA30**

Limit switches

PS

Agricultural machinery needs reliable and durable parts and components able to work long hours in difficult outdoor conditions, exposed to every kind of stress.

Carlo Gavazzi offers a comprehensive range of components for most applications in agricultural and earth-moving vehicles, from passive magnetic pick up sensors (PA2PK) to inductive proximity sensors.

The pick up sensors detect and measure the speed of phonic or toothed wheels and generally of any rotating device built in a ferromagnetic material and provided with slots and cogs, for example in engines and in tractors.

Inductive sensors are used for non-contact measurements - for example to count revolutions of the axle in machinery or to monitor the bucket position in a backhoe loader. Safety and positional mechanical switches in different versions and configurations are also available.

Ultrasonic sensors (UA series) are also used to monitor sprayer heights in self-propelled row-crop sprayers. A particular application of ultrasonic sensors with analog output is the control of the driving direction of the wagons or a motorized chassis - equipped with one or more fixed or mobile platforms - for example - for harvesting fruit.



Silos



Capacitive sensors

**CB32
VC11/12**

Capacitive sensors

**CA30CAN/CAF
CA18CAN/CAF
EC30**

Conductive level controllers / probes

**CLD
CLP
CLH**

1-phase solid state switches

**RGC1
RGS1**

Energy analysers

**EM340
EM24**

Timers

**DAA51
DMB51**



Carlo Gavazzi offers very efficient means for liquid and solid level measurement, both in large silos and in small storage containers.

Our 4th generation TRIPLESIELD™ capacitive sensors are designed to detect objects with a dielectric constant (DC) of as low as 1.5. The CA18 and CA30 CAN/CAF sensors are excellent for accurate measurement of dry grain regardless of degree of humidity. The sensor provides a stable and precise signal of yield per unit area.

Knowing these areas makes it easy to adjust the amount of fertilizers and herbicides in exactly the right way. As a result, cost can be reduced and the environmental impact minimized. The

capacitive sensors EC30 (AC version) have a long sensing distance that allows easy detection of the grain.



The VC11/12 sensors are available in multivoltage power supply with relay output and used in many applications for the agriculture business.

The conductive level program by Carlo Gavazzi comprises a complete range of intelligent conductive level controllers for liquids such as in slurry tanks (CL-series), CLH electrode probes (3 or 5 electrodes).

Various adjustment possibilities enable the controller to perform filling operations, emptying operations or a combination of the two.

Agriculture

Feed distribution systems



Magnetic sensors	Capacitive sensors	Capacitive sensors	Photoelectric sensors	Inductive sensors	1 & 3-phase proportional controllers	Soft starters	Switching power supplies
S series	CA18CL CA30CLN	VC11/12 CB32	PD30ET PA18/PH18	ICS12 ICS18 ICS30	RGC1P RGC2P RGC3P	RSGD RSBT	SPD SPPC SPM

Feeding distribution systems are critical to the quality and safety of farms with pig, poultry and dairy sectors. It is important to feed all the chickens at the same time and manual handling is eliminated.

The distribution is controlled by sensors (capacitive, inductive, photoelectric), normally combined with solid state relays and soft starters. Carlo Gavazzi capacitive level sensors are excellent for use in the agricultural sector (detection of feed, fluids etc.). The VC11/12 sensors are able to directly drive a contactor or a small motor.

The PD30 Stainless steel sensors work perfectly even in the harshest environments. The high-quality stainless

steel housing guarantees maximum mechanical resistance, and prescribed cleaning schedules are smoothly met without costly machine downtime. Ultrasonic sensors or capacitive sensors control the levels in the silos and monitor emptying to ensure the efficiency of the process. Carlo Gavazzi soft starters (RSGD) soft start and soft stop pumps, screw feeders, ventilators as well as chillers (RSBT).

Temperature control in animal farms is optimised with the RGC1P proportional controller which, through an analog input, regulates the power of heating lamps. Furthermore, RGC3P (in special version) is used for optimal speed control of ventilators in egg incubators.



Irrigation



Dupline® digital I/O modules	Dupline® converters	Conductive level controllers / probes	3-phase pump and ventilators soft starters	Timers	Monitoring relays
GH3440 4412 GH6440 4412	GH3485 0000	CLD CLP CLH	RSWT	DAA51 DMB51	DPA51 DPB52



Traditional irrigation systems are characterized by complex and expensive wiring. The Carlo Gavazzi Dupline® irrigation bus reduces installation costs and increases flexibility in agricultural irrigation systems, where the valves are usually distributed over a large area. Any type of irrigation controller, whether it is a PLC, PC or dedicated controller, can use Dupline® as a remote I/O system. The wiring topology is completely free, with no limitation to the number and length of branches. The Dupline® Fieldbus is the ideal system to control levels, monitor pumps and activate valves over a large area and from a distance. In centrifugal pump applications the

softstarter RSWT series represent a plug and play solution to easily replace star-delta starters and contactors. This soft starter only requires 1 setting for the ramp-up and ramp down time for the pump. All the rest is taken care of by the RSWT self-learning algorithm that is active during every start and makes sure that the pump is started within the set time, whilst optimising the pump starts and stops. The Carlo Gavazzi product range includes a variety of automation components suitable for use in irrigation, landscaping and greenhouses: monitoring relays, inductive, capacitive and ultrasonic sensors, digital panel meters and energy meters.

Agriculture

Our product range

Capacitive sensors



CA18CAN/CAF / CA30CAN/CAF

- Dimensions: M18 / M30
- Plastic housings, DC versions
- Adjustable sensing distance up to 20 mm flush and 30 mm non-flush
- Protection: short circuit, transient and reverse polarity
- Degree of protection: IP67, IP68 and IP69K
- Approvals/Marks: CE - cULus - Ecolab

MAIN FEATURES

- 4th generation TRIPLESIELD™ technology
- Dust and humidity compensation
- Dust and temperature alarm outputs
- Increased temperature stability
- Sensing face can withstand temperatures up to 120°C

Capacitive sensors




CA30CLN

- Level sensor for solid, fluid or granulated substances
- Dimensions: M30
- Adjustable sensing distance: 4-12 mm
- Thermoplastic polyester housing
- Multi voltage supply 20.4 to 255 VAC/DC
- Approvals/Marks: CE - cULus

MAIN FEATURES

- Available with/without built-in time delay
- Dust and humidity compensation
- Rear side with integrated trimmer shaft
- Laser printing of main specifications on the sensor surface

Capacitive sensors



VC11/12

- Capacitive level sensors for solid, fluid or granulated substances
- Dimensions: Ø32
- Adjustable sensing distance: 4 - 12 mm
- Multivoltage supply: 20.4 to 255 VAC/DC
- Approvals/Marks: CE - cULus

MAIN FEATURES

- New back-part with integrated trimmer shafts
- SPDT relay output
- Time delay on operate or release

Capacitive sensors ATEX version



CB32

- TRIPLESIELD™ sensor protection
- Adjustable sensing distance: 4 - 20 mm
- Dimensions: Ø32
- Capacitive level sensors for solid, fluid or granulated substances
- Protection transients and reverse polarity
- Approvals/Marks: CE

MAIN FEATURES

- Approved acc. to ATEX directive operation in potential explosive dusty
- Relay output
- With or without adjustable time delay

Capacitive sensors



CA18CL

- TRIPLESIELD™ sensor protection
- Sensing distance: 0.5 - 12 mm (M18)
- Plastic housing, AC versions
- Automatic detection of NPN or PNP load
- Selectable "make or break" switching by means of Teach function
- Approvals/Marks: CE - UL - CSA

MAIN FEATURES

- Teach-in of sensing distance via push-button or COM-input
- Humidity compensation
- Protection: short-circuit, transients and reverse polarity

Capacitive sensors



EC30

- TRIPLESIELD™ sensor protection
- Sensing distance up to 25 mm
- Dimensions: M30
- Plastic housing, AC versions
- Approvals/Marks: CE - UL - CSA

MAIN FEATURES

- Detection of e.g., corn or feed
- Sensing face can withstand temperatures up to 120°C
- Protection: short circuit, transient and reverse polarity

Our product range

Pick up sensors



PA2PK

- Dimensions: diameter M20 x 1.5 length 60, 70, 107 mm
- Pulse output function
- Cylindrical nylon with 30% glass fibre
- Protection degree IP65
- Approvals/Marks: CE

MAIN FEATURES

- AMP connector Supersel
- Suitable for applications where the measurement of gear speed is required.
- Operating frequency > 100 Hz

Ultrasonic sensors



UA18 / UA30

- Dimensions: M18, M30
- Ultrasonic sensors with integrated amplifier providing a digital and/or analog output and integrated amplifier
- Up to 6 m sensing distance
- Switching output with two setpoints
- Housing material: plastic or AISI316L Stainless Steel
- Approvals/Marks: CE - cULus - CSA

MAIN FEATURES

- Excellent EMC performance and precision
- Detects clear, transparent and shiny targets, solid objects, liquid or granules.
- Protection: short circuit, transient and reverse polarity

Conductive level controllers / probes



CLD / CLP / CLH

- 17.5mm slim housing, 22.5 mm & 35 mm housing available
- Multiple filling and emptying functions
- 24-240 VAC/DC (CLD2EB1BU24)/24 VDC, 115 VAC, 230 VAC
- Flexible modular probes up to 5 electrodes (CLH5)
- Extendible probes for longer length

MAIN FEATURES

- Wide operational supply voltage range
- Slim compact housing
- Wide sensitivity adjustment 250 Ω to 500 KΩ
- Cascading amplifiers for more levels (CLP2FA)

Photoelectric sensors



PD30ET

- World standard housing style 11 x 31.5 x 21 mm
- Supply voltage: DC 4-wire
- Output: NPN/PNP NO+NC
- Sensor types: D, B, R, P and T
- Connectivity: Cable or M8 connectors
- Approvals/Marks: CE - cULus (UL508, CSA C22.2) - ECOLAB

MAIN FEATURES

- Stainless Steel housing AISI 316L
- Resistant to high-pressure washdown, aggressive cleaning agents.
- IP67, IP68, IP69K, NEMA type 1, 2, 4, 4x, 5, 6, 6P
- Protection: reverse polarity, short circuit and transients

Photoelectric sensors



PA18

- Standard M18 cylindrical housing
- Power supply: 10 to 30 VDC
- Separate models available for NPN or PNP outputs
- Sensing types: Diffuse reflective, BGS, Pol. Retro-reflective, Through beam
- Sensitivity adjustment by potentiometer
- Approvals/Marks: CE - cULus

MAIN FEATURES

- IP69K / ECOLAB approved / CE marking / cULus approved acc. to UL508
- Diagnostic LED indication (Green and Yellow LED)
- Short-circuit, reverse polarity and overload protection

Photoelectric sensors



PH18

- Square sensor with M18 front
- Power supply: 10 to 30 VDC
- Separate models available for NPN or PNP outputs
- Sensing types: Diffuse reflective, BGS, Pol. Retro-reflective, Through beam
- Sensitivity adjusted by potentiometer
- Approvals/Marks: CE - cULus

MAIN FEATURES

- IP69K / ECOLAB approved / CE-marking / cULus approved acc. to UL508
- Diagnostic LED indication (Green and yellow LED)
- Short circuit, reverse polarity and overload protected

Agriculture

Our product range

Inductive sensors



ICB12 / ICB18 / ICB30

- M12, M18 and M30 Nickel-brass housing in short or long barrel lengths
- Standard, double and triple distance sensing ranges
- 3-wire and 4-wire versions
- Two metres oil resistant PVC cable or M12 plug version
- Approvals/Marks: CE - cULus - cCSAus

MAIN FEATURES

- High precision and reliability thanks to the microprocessor technology
- Short-circuit and overload LED indication
- Laser engraved information on the front cap, permanently legible

Inductive sensors



ICS12 / ICS18 / ICS30

- M12, M18 and M30 stainless steel housing
- Sensing distance from 2 mm up to 22 mm
- Degree of protection: IP67, IP68 and IP69K
- Approvals/Marks: CE - cULus - cCSAus - ECOLAB

MAIN FEATURES

- Certified compatibility with most of the detergents and disinfectants available on the market
- Short-circuit and overload LED indication
- Extended temperature range: -40°C to +80°C (-40°C to +85°C for ICS30)

Magnetic sensors



S series

- Type: rectangular plastic housing
- Dimensions: 79 x 21.2 x 11.5 mm
- Side operated
- Operating temperature -25°C to 75°C
- Protection degree IP67

MAIN FEATURES

- Several operating distances thanks to wide range of magnetic units (CL series)
- Easy and fast mounting

1-phase solid state switches



RGS1 / RGC1

- Product width: 17.5 mm up to 70 mm, DIN-rail or panel mount
- Ratings: up to 660 VAC, 90 AAC, 18000 A²s
- Integrated output overvoltage protection
- Control input ranges: 4-32 VDC, 20-275 VAC (24-190 VDC)
- Approvals/Marks: CE - cULus (RGC), cURus (RGS), CSA (RGS), VDE - GL (RGC up to 30 AAC)

MAIN FEATURES

- Integrated heatsink (RGC), without heatsink (RGS)
- 100 kA short circuit current rating
- Optional over temperature protection (RGC)

1 and 3-phase proportional controllers



RGC1P / RGC2P / RGC3P

- Product width: 35 mm up to 70 mm, DIN or panel mount
- 1-ph with heatsink (RGC1P) or for panel mount [RGS1P], 3-ph with heatsink (RGC2P, RGC3P)
- Ratings: up to 660 VAC, 90A (1-ph), 75A/pole (2-ph), 65A/pole (3-ph)
- Control input: 0-20 mA, 4-20 mA, 12-20 mA, 0-10 VDC, 0-5 VDC, 1-5 VDC
- Approvals/Marks: CE - cULus - UR (RGS1P) - CSA (RGS1P)

MAIN FEATURES

- Selectable switching modes
- Integrated overvoltage protection
- Monitoring for SSR and load circuit malfunctions (RGC2P, RGC3P)

3-phase scroll compressor soft starters



RSBD / RSBT

- Enhanced current reduction capability with patented auto-adaptive algorithm
- Motor rating: 3-phase up to 45 kW @ 400 V
- Integrated diagnostic functions
- 2- and 3-phase controlled solutions
- Approvals/Marks: cUL listed

MAIN FEATURES

- Plug and play: no user settings required
- Typically > 50% scroll compressor inrush current reduction
- Internally bypassed and internally supplied

Our product range

3-phase general purpose soft starters



RSGD

- Operational voltage range: 187 - 440 VAC, 187 - 660 VAC
- Operational current range: 12 AAC up 100 AAC
- Control voltage: 24 VAC/DC, 110 - 400 VAC
- Serial communication (Modbus 2-wire) [RSGD 75mm models]
- Approvals/Marks: cULus, CCC, EAC

MAIN FEATURES

- Easy to use and set-up
- Self-learning algorithm to adapt to different loads
- Auxiliary relays for top of ramp and alarms

3-phase pumps and ventilators soft starters



RSWT

- Motor rating: up to 45 kW (90 A)
- 3-phase controlled & internally bypassed
- Operational voltage: RSWT40: 220 - 400 VAC, RSWT60: 220 - 600 VAC
- PTC input, Alarm - Top of Ramp - Run relay indication
- Approvals/Marks: cULus, CCC

MAIN FEATURES

- Easy to use and setup
- Self-learning algorithm to improve pump starts/stops
- Integrated overload protection (Class 10)

Monitoring relays



DPA51

- Dimensions: 81 x 17.5 x 67.2 mm DIN-rail housing
- Phase sequence and loss relay
- 3-phase AC (own power supply); regenerated voltage
- Power supply from 208 to 480 VAC
- Approvals/Marks: CE - UL - CSA - CCC

MAIN FEATURES

- Protection from reverse running and phase loss
- 17.5 mm width: the smallest in the market
- Plug and play: no settings needed

Monitoring relays



DIA53

- Dimensions: 81 x 17.5 x 67.2 mm DIN-rail housing with 12 mm hole for current measurement
- Current monitoring relay with built-in current transformer
- 20, 50 or 100 A full scale
- Self powered
- Approvals/Marks: UL - CSA - CCC

MAIN FEATURES

- 2-wire connection
- Knob adjustable setpoint
- Integrated solid state NPN PNP output

Monitoring relays



DPB52

- Dimensions 81 x 17.5 x 67.2 mm DIN-rail housing
- Phase sequence and phase loss, regenerated V detection
- 3 phase AC (own power supply)
- Power supply from 125 to 624 VAC (rated 208 to 480 VAC)
- Approvals/Marks: UL - CSA - CCC

MAIN FEATURES

- Overvoltage/undervoltage setting with alarm ON delay
- 1 DIN module width. Suitable NORM panels
- Switch mode power supply

Monitoring relays



DIB02 / PIB02

- Dimensions: 22.5 mm for DIN-rail (DIB) or 35.5 mm for plug in (PIB)
- Overcurrent or undercurrent detection
- DC current measurement by means of external Shunt
- Power supply 115/230 VAC, 24/48 VAC, 24 VDC, 48 VDC
- Adjustable time delay

MAIN FEATURES

- Motors protection from overload
- DC or AC current measurement
- 3-phase overcurrent measurement with MP3 CT

Agriculture

Our product range

Current transformers




E83-2050

- DIN-rail or surface mounting 22.5 mm Euronorm housing with 12 mm hole for current measurement
- AC current transformer with 4-20 mA DC secondary
- 1-phase AC current measurement
- Power supply from 10 to 40 VDC
- Approvals/Marks: UL

MAIN FEATURES

- 7 knob selectable ranges from 5 to 50 AAC
- Easy interface to PLC or monitoring relays

Current transformers



CTD / TADK

- CTD: currents from 40 to 4000 A
- TADK2: 1 - 250 A
- Removable panel fixing clips
- DIN-rail and panel mounting facility
- Double screw terminals (CTD)
- Sealable covers
- Case: ABS, self-extinguishing level UL 94 V-0
- Accuracy class: 0.5

MAIN FEATURES

- Wound primary / solid core or split-core
- Compliance with IEC 60185, VDE 0414-1 regulations
- Removable DIN-rail mounting holder

Timers



DAA51 / DMB51

- Dimensions: 81 x 17.5 x 67.2 mm DIN-rail housing
- Delay on operate function (DAA), multifunction (DMB)
- Combined AC and DC power supply
- Repeatability: < 0.2%
- Approvals/Marks: UL - CSA - RINA

MAIN FEATURES

- Delay on operate/release; interval (manual/automatic start)
- Double interval; symmetrical recycler (ON or OFF first)
- Timing range from 0.1 s to 100 h

Timers



FMB01 / FAA

- Dimensions: 48 x 48 mm housing for 11 pin socket or panel mounting
- Multifunction timer with 7 functions
- DPDT output
- Universal power supply
- Approvals/Marks: cUR - CSA

MAIN FEATURES

- Front knob adjustable time setting
- Selectable time ranges from 0.05 s to 300 h
- Delay on operate/release, ON/OFF first symmetrical recycle, single/double interval on trigger open/close

3-phase power transducers



CPT

- Dimensions: 83.5 x 45 x 98.5 mm DIN-rail housing
- Accuracy 0.5 % (voltage, current)
- Measurement by CT and VT
- Front protection degree IP20
- Analogue, digital, pulse or serial outputs available

MAIN FEATURES

- Compact size power transducer
- Provides electrical variables set to a PLC to manage compressors and other loads
- Suitable for on-board panel installation

3-phase energy analysers for direct current up to 65A



EM340

- 3 DIN modules
- Backlit touch LCD
- Measurement of voltage, current, power, power factor and frequency
- Bi-directional energy metering, 3x 8-digit, cl. B (EN50470)
- Measuring inputs: 230 to 400 V_{LL} AC, 65A
- Approvals/Marks: CE - MID (PFA and PFB)

MAIN FEATURES

- Self-powered
- Dual tariff management
- Pulse output or RS485 Modbus or M-Bus port
- Sealable terminal covers

Our product range

3-phase energy analysers



EM24

- 3-phase energy analyser with direct connection
- Direct connection up to 65 A or by CT
- Dimensions: 4-DIN-rail module housings
- Class B (EN50470)
- Pulse open collector output
- Modbus or M-bus communication port

MAIN FEATURES

- Direct measurement in a very compact housing to save space
- Suitable for measuring generated and consumed energy
- On request, MID annex D certification available
- M-bus port integrated in the meter without external gateways

Dupline® digital I/O modules



GH3440 4412

- Module for controlling 3-wire latching valves
- 2 outputs to open and close valve
- 2 inputs for e.g., pulse counting, tamper switch or status feedback
- Supplied by bus - no external power needed
- Valve closes in case of bus fault

MAIN FEATURES

- Built-in microcontroller for correct coil-pulsing and charge monitoring
- Valve closes in case of bus fault

Dupline® valve controls



GH6440 4412

- Module for controlling 3-wire latching valves
- 2 outputs for open and close valve
- 2 inputs for e.g. pulse counting, tamper switch or status feedback
- Built in charge capacitor, gas arrestor and microcontroller

MAIN FEATURES

- Can be buried in the ground at the actual valve position
- Supplied by bus – no external power needed

Dupline® converters



GH3485 0000

- Generates 28 V Hi-Line signal
- Supplies and controls up to 64 valve I/O modules over two wires
- LED-indications for Dupline® carrier, Hi-Line carrier and supply

MAIN FEATURES

- Built-in Gas-arrestor for lightning protection
- Up to 7 km transmission distance

Dupline® test units



GHTU8

- Portable test unit
- 12 key tactile keyboard
- Dual group reading
- Analog BCD reading

MAIN FEATURES

- Monitoring of Hi-line channel status with LCD display
- Designed as part of the Dupline® irrigation concept

Switching power supplies



SPD

- DIN-rail housing
- Short circuit protection
- 1-phase AC
- Rated input voltage: 115/230 VAC selectable 100/240 VAC
- Approvals/Marks: UL - cUL listed - TÜV - CE

MAIN FEATURES

- Overload protection
- Parallel versions available
- High efficiency

Agriculture

Our product range

Low profile power supplies



SPM

- Compact din-rail housing - 1/3/4/5 Din width
- Universal input from 90 - 264 VAC
- Integrated short-circuit and overload protection with built-in input filters
- High efficiencies of up to 89%
- Approvals/Marks: CE - cULus - TUV

MAIN FEATURES

- Compact design for installation with in distribution box with ratings up to 100 W
- Intuitive visual and electrical indications
- Selected models comes with UL 1310 Class 2 classification and ISA 12.12.1 CLASS I DIV2

Switching power supplies



SPPC: Enclosed type 25 W...320 W

- Miniature size: 25/35/50 W
- Medium size: 75/100/150 W
- Compact size: 200/240/320 W
- Built-in active PFC (Power Factor Protection) from 100 W
- Output protections: SCP/OLP/OPP

MAIN FEATURES

- PCB soldering side with conformal coating (miniature size)
- 105°C long life electrolytic capacitor and wide operating ambient temperature -25°C ~ 70°C (medium and compact size)

Switching power supplies



SPPC: Enclosed type 480 W...800 W

- Dimensions: 218 x 116.5 x 41 mm
- Universal AC input/ Full range
- Built-in active PFC function, PF>0.96
- Output protection: OVP/OLP/SCP/OPP/OTP
- Built in AC inrush current limiting circuit (<20 A)
- Built in Remote Sense Function

MAIN FEATURES

- Built in fan speed control and over temperature protection
- Wide operating ambient temperature (-30°C ~ 70°C)
- Build in DC OK signal

DC UPS controller



SPUC

- Up to 30 A UPS controller
- 12 V and 24 V versions
- Outputs for Device OK, Battery OK and battery Low.
- DIN rail battery accessory available up to 7.2 A/h
- Approvals/Marks: CE - UL

MAIN FEATURES

- To be used in addition to 12 or 24 V power supply
- Front 30 A replaceable fuse
- Plug and play: no settings needed

DC UPS battery charger



SPUBC

- Power supply, UPS and battery charger "All in one"
- 24 VDC 5 A output
- Power boost up to 2 times rated output, permanent
- Built in battery diagnosis
- Approvals/Marks: CE - UL

MAIN FEATURES

- Power supply independent from charger.
- Remote indication for battery operation and battery low
- "Start from battery" and "Empty battery charging" features

Limit switches



PS

- Material: plastic, metal
- Horizontal / vertical control available
- Minimum actuation force / torque
- Approvals/Marks: CE - UL - CSA

MAIN FEATURES

- Mechanical life > 15,000,000 cycles
- Precise operating point

OUR SALES NETWORK IN EUROPE

AUSTRIA

Carlo Gavazzi GmbH
Ketzergasse 374,
A-1230 Wien
Tel: +43 1 888 4112
Fax: +43 1 889 10 53
office@carlogavazzi.at

BELGIUM

Carlo Gavazzi NV/SA
Mechelsesteenweg 311,
B-1800 Vilvoorde
Tel: +32 2 257 4120
Fax: +32 2 257 41 25
sales@carlogavazzi.be

DENMARK

Carlo Gavazzi Handel A/S
Over Hadstenvej 40,
DK-8370 Hadsten
Tel: +45 89 60 6100
Fax: +45 86 98 15 30
handel@gavazzi.dk

FINLAND

Carlo Gavazzi OY AB
Ahventie, 4 B
FI-02170 Espoo
Tel: +358 9 756 2000
myynti@gavazzi.fi

FRANCE

Carlo Gavazzi Sarl
Zac de Paris Nord II, 69, rue de la Belle Etoile,
F-95956 Roissy CDG Cedex
Tel: +33 1 49 38 98 60
Fax: +33 1 48 63 27 43
french.team@carlogavazzi.fr

GERMANY

Carlo Gavazzi GmbH
Pfnorstr. 10-14
D-64293 Darmstadt
Tel: +49 6151 81000
Fax: +49 6151 81 00 40
info@gavazzi.de

GREAT BRITAIN

Carlo Gavazzi UK Ltd
4.4 Frimley Business Park,
Frimley, Camberley, Surrey GU16 7SG
Tel: +44 1 276 854 110
Fax: +44 1 276 682 140
sales@carlogavazzi.co.uk

ITALY

Carlo Gavazzi SpA
Via Milano 13,
I-20020 Lainate
Tel: +39 02 931 761
Fax: +39 02 931 763 01
info@gavazziacbu.it

NETHERLANDS

Carlo Gavazzi BV
Wijkermeerweg 23,
NL-1948 NT Beverwijk
Tel: +31 251 22 9345
Fax: +31 251 22 60 55
info@carlogavazzi.nl

NORWAY

Carlo Gavazzi AS
Melkeveien 13,
N-3919 Porsgrunn
Tel: +47 35 93 0800
Fax: +47 35 93 08 01
post@gavazzi.no

PORTUGAL

Carlo Gavazzi Lda
Rua dos Jerónimos 38-B,
P-1400-212 Lisboa
Tel: +351 21 361 7060
Fax: +351 21 362 13 73
carlogavazzi@carlogavazzi.pt

SPAIN

Carlo Gavazzi SA
Avda. Iparraguirre, 80-82,
E-48940 Leioa (Bizkaia)
Tel: +34 94 480 4037
Fax: +34 94 431 6081
gavazzi@gavazzi.es

SWEDEN

Carlo Gavazzi AB
V:a Kyrkogatan 1,
S-652 24 Karlstad
Tel: +46 54 85 1125
Fax: +46 54 85 11 77
info@carlogavazzi.se

SWITZERLAND

Carlo Gavazzi AG
Verkauf Schweiz/Vente Suisse
Sumpfstrasse 3,
CH-6312 Steinhausen
Tel: +41 41 747 4535
Fax: +41 41 740 45 40
info@carlogavazzi.ch

OUR SALES NETWORK IN THE AMERICAS

USA

Carlo Gavazzi Inc.
750 Hastings Lane,
Buffalo Grove, IL 60089, USA
Tel: +1 847 465 6100
Fax: +1 847 465 7373
sales@carlogavazzi.com

CANADA

Carlo Gavazzi Inc.
2660 Meadowvale Boulevard,
Mississauga, ON L5N 6M6, Canada
Tel: +1 905 542 0979
Fax: +1 905 542 22 48
gavazzi@carlogavazzi.com

MEXICO

Carlo Gavazzi Mexico S.A. de C.V.
Calle La Montaña no. 28, Fracc. Los Pastores
Nauclan de Juárez, EDOMEX CP 53340
Tel & Fax: +52.55.5373.7042
mexicosales@carlogavazzi.com

BRAZIL

Carlo Gavazzi Automação Ltda.Av.
Francisco Matarazzo, 1752
Conj 2108 - Barra Funda - São Paulo/SP
Tel: +55 11 3052 0832
Fax: +55 11 3057 1753
info@carlogavazzi.com.br

OUR SALES NETWORK IN ASIA AND PACIFIC

SINGAPORE

Carlo Gavazzi Automation Singapore Pte. Ltd.
61 Tai Seng Avenue #05-06
Print Media Hub @ Paya Lebar iPark
Singapore 534167
Tel: +65 67 466 990
Fax: +65 67 461 980
info@carlogavazzi.com.sg

MALAYSIA

Carlo Gavazzi Automation (M) SDN. BHD.
D12-06-G, Block D12,
Pusat Perdagangan Dana 1,
Jalan PJU 1A/46, 47301 Petaling Jaya,
Selangor, Malaysia.
Tel: +60 3 7842 7299
Fax: +60 3 7842 7399
sales@gavazzi-asia.com

CHINA

Carlo Gavazzi Automation
(China) Co. Ltd.
Unit 2308, 23/F.,
News Building, Block 1, 1002
Middle Shennan Zhong Road,
Shenzhen, China
Tel: +86 755 83699500
Fax: +86 755 83699300
sales@carlogavazzi.cn

HONG KONG

Carlo Gavazzi Automation
Hong Kong Ltd.
Unit 3 12/F Crown Industrial Bldg.,
106 How Ming St., Kwun Tong,
Kowloon, Hong Kong
Tel: +852 23041228
Fax: +852 23443689

OUR COMPETENCE CENTRES AND PRODUCTION SITES

DENMARK

Carlo Gavazzi Industri A/S
Hadsten

MALTA

Carlo Gavazzi Ltd
Zejtun

ITALY

Carlo Gavazzi Controls SpA
Belluno

LITHUANIA

Uab Carlo Gavazzi Industri Kaunas
Kaunas

CHINA

Carlo Gavazzi Automation (Kunshan) Co., Ltd.
Kunshan

HEADQUARTERS

Carlo Gavazzi Automation SpA
Via Milano, 13
I-20020 - Lainate (MI) - ITALY
Tel: +39 02 931 761
info@gavazziautomation.com



CARLO GAVAZZI
Automation Components

Energy to Components!

www.gavazziautomation.com

