



My Account

🗎 Print

Check Pricing & Availability

Contact Us About This Product

▶ Product Feature Selector

What can we help you find?

📴 Share

Quick Links

▶ Search for Tooling




Email

Products Industries About TE Support Center Resources

Home > Products > Relays > Product Feature Selector > Product Details

# FCA-210-CY4 Product Details



FCA-210-CY4 (1617752-6)

TE Internal Number: 1617752-6

Active

# Military/Aerospace Mid-Range Relays

Not EU RoHS or ELV Compliant

#### Product Highlights:

- FCA 10-25 Amp Relay Series
- DC Actuating System
- Coil Rated Voltage = 28 VDC
- Coil Resistance = 320 Ω
- Contact Arrangement = 2 Form C, DPDT, 2 C/O

View all Features









#### **Documentation & Additional Information**

#### Product Drawings:

MSD RELAY (PDF, English)

### Catalog Pages/Data Sheets:

None Available

## **Product Specifications:**

None Available

#### **Application Specifications:**

None Available

### **Instruction Sheets:**

None Available

## CAD Files:

None Available

#### Additional Information:

Product Line Information

#### Additional Product Images:

- Dimensional Drawing
- Wiring Diagram
- Terminal Type

#### Related Products:

Tooling

List all Documents

# Product Type Features:

- Series = FCA 10-25 Amp Relay
- Terminal Configuration = Solder Hook

## **Electrical Characteristics:**

- Actuating System = DC
- Coil Rated Voltage (VDC) = 28
- Coil Resistance (Ω) = 320.
- Current Rating (A) = 10
- Shock = 200G's, 6ms
- Vibration = 30G's, 33 to 3000Hz

## **Termination Features:**

- Terminal Plating = Tin-Lead
- Auxiliary Contacts = Without

## **Body Features:**

Mount Type = Raised Vertical Flange Mount

## Contact Features:

Enclosure Type = Hermetically Sealed

## Configuration Features:

- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Coil Suppression Diode = With
- Coil Magnetic System = Polarized, Monostable

# Industry Standards:

- Government/Industry Qualification = No
- RoHS/ELV Compliance = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Not suitable for lead free processing

## Other:

Brand = CII

Corporate Information

Who We Are Investors News Room Supplier Portal

Careers

Quick Links

Product Features (Please use the Product Drawing for all design activity)

Check Distributor Inventory

Cross Reference

Find Documents & Drawings

Product Compliance Support Center

Site Map

Customer Support

Email or Chat With Us Find a Phone Number Search Knowledge Base

Manage your Account

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address













