



Datasheet

Art.No. 96.032.4055.7

Connector RST20I3S S1 ZR1 VH GN0

Connector RST20i3, 3 pole, male, screw connection, 250V/20A, for cable diameters 6-10 mm, color of coding: green, color of housing: black



Art.No.	96.032.4055.7
EAN	4015573875104
Order unit	1 pieces

Approvals









Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Mechanical coding	Yes
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Leaves green
Marking of poles	1, 2, PE
Color of housing inclusive strain relief	Black





Connection Data

Cable diameter	10 mm
Cable diameter 2	6 mm
Cable diameter 3	10 mm
Connection cross section solid	6 mm ²
Cross section solid 2	0.75 mm ²
Connection cross section stranded max.	6 mm²
Cross section stranded 2	0.75 mm²
Terminations per pole	1
Connection cross section stranded min.	0.75 mm ²
Connection cross section stranded max.	6 mm²

Model

Model	male
Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69K

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	80.4 mm
Width	34.6 mm
Height	34.6 mm

Classification

ECLASS 8.1	27440605: Plug-in connector for plug-in building installation
ETIM 5.0	EC002560: Plug-in connector for plug-in building installation
ETIM 4.0	EC002560: Plug-in connector for plug-in building installation





Drawings

