


Honeywell Sensing and Control

Home> Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

■ Order Product and **Get Support**

- U.S. Authorized **Distributors**
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

101TL2-51



TL Series Toggle Switch, 1 pole, 3 position, IWTS (16-20 Gage) terminal, Standard Lever, Military Part Number MS27784-32

Keyword Search Search for product and support information. All Sensing and Contro Product Search Part number search: Use (*) to expand search

Specification Search

Features

Qualified to MILS-3950 Environmentproof sealing 1,2, and 4 pole circuitry Standard and pull-to-unlock levers 2 and 3 position, maintained and momentary toggle action Temperature range:-85? F to +160? F Completely sealed switching chamber Step-design case provides added space between terminals to help prevent shorting UL recognized, CSA certified CE approved

Actual product appearance may vary.

Potential Applications

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

Description

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pulto-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Supporting Documentation

Accessory: Lever **Sleeve**

▲ Accessory: Seals

Accessory: Nuts



Product Specifications	
Circuitry/Operating action	Keyway Momentary Center Position Position Position 1 2 3 1 2 3 1 2 3
	ON OFF ON
Product Type	MICRO SWITCH™ Toggle Switch
Ampere/Voltage Range (Resistive Load)	0.5 A at 250 Vdc,0.75 A at 115 Vdc,0.5 A to 6 A at 0.5 Vac to 230 Vac,0.5 A to 7.5 A at 0.5 Vdc to 28 Vdc
Circuitry	SPDT
Action	3 position
Mounting	Bushing 15/32 in
Termination	IWTS (16 - 20 Gage)
Military Part Number	MS27784 -32
Lever Type	Standard
UL/CSA Rating Code	L192: 10 A - 125, 250, 277 Vac; 1/4 Hp - 125 Vac; 1/2 Hp - 250, 277 Vac; 3 A - 125 Vac "L"
Comment	Silver cadmium oxide contacts
Availability	Global
UNSPSC Code	30211908
UNSPSC Commodity	30211908 Toggle switches
Series Name	TL