

Pushbutton, 18.2 mm, screw terminal, momentary contact function, 2 NO, bezel red



fields of application

- Mechanical and system engineering
- Model construction
- Home technology

description

Pushbutton with mounting hole diameter 18.2 mm, non-illuminated, 250 V / 4 A

technical data

➤ general

illuminated	No
Bezel color	red
Collar shape	round
Operating temperature, min.	-25 °C
Operating temperature, max.	85 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	90 °C
Packaging	Box
Packaging unit	100 pcs.
Operating life	50,000 Cycles
Degree of protection, front side, according to DIN EN 60529	IP40 IP65 IP65 with sealing cap
RoHS compliant	Yes
REACH compliant	Yes

➤ mounting diameters

Mounting hole	18.2 mm
Mounting depth	34 mm
Installation height	10.5 mm

direct links

- [RAFI eCatalog](#)

Outside dimension, width 22 mm

➤ **mechanical data**

Actuation function momentary contact function

Operating force, min. 9.5 N

Operating travel, max. 5 mm

Contact function 2 NO

Contact system Bridge-sliding contact

Contact material Silver

Fixing Threaded ring

Terminal on the rear Screw terminal

➤ **electrical data**

Rated voltage, max. 250 V

Rated current, max. 2 A