



## **Hook and Loop Fasteners**

## FO, FOL, FOS and FOR Series

## New version available — UL94V-2 rated material

- High-quality Hook & Loop Fasteners designed specifically for Thomas & Betts
- Enables quick and convenient bundling of data and fiber optic cables
- · Sizes available to accommodate varying bundle diameters
- Screw and adhesive mounting bases provide multiple mounting options



Wrap pre-determined bundle diameters using the convenient slotted head!

**FO Series Loop Ties** 



Polymer buckles provide added strength and stability.

**FOL Series Buckle Ties** 



Pre-cut lengths make bundling a cinch!

**FOS Series Strip Ties** 



Rolled hook and loop material enables custom cut lengths, avoiding waste.

FOR Series Rolled Hook and Loop

Fasteners available in these colours: Black, Brown, Red, Orange, Yellow, Green, Blue, Grey, and White.
Please consult Regional Sales Office for delivery and availability.

Min. Tensile Strength (lb./N)	Max. Bundle Dia. (in./mm)	Length (in./mm)	Width (in./mm)	Std. Pkg.
40/177.9 50/222.4	2.0/50.80	9/228.6	0.50/12.7	10
			0.75/19.05	
	3.5/88.90	13/330.2	0.50/12.7	
			0.75/19.05	
es				
50/222.4	3.0/76.20	12/304.8	0.75/19.05	10
	5.0/127.00	18/457.2		
;				
50/222.4	1.5/38.10	6/152.4	_	10
	3.2/81.28	12/304.8		
	5.0/127.00	18/457.2		
ook and Loop				
50/222.4	Various	180/4572	_	1
	Strength (lb./N)  40/177.9  50/222.4  es  50/222.4  50/222.4	Strength (lb./N)  40/177.9  2.0/50.80  50/222.4  3.5/88.90  es  50/222.4  3.0/76.20  5.0/127.00  1.5/38.10  3.2/81.28  5.0/127.00  pok and Loop	Strength (lb./N) Bundle Dia. (in./mm) Length (in./mm)  40/177.9 2.0/50.80 9/228.6  50/222.4 3.5/88.90 13/330.2  es  50/222.4 3.0/76.20 12/304.8 5.0/127.00 18/457.2  50/222.4 3.2/81.28 12/304.8 5.0/127.00 18/457.2  pook and Loop	Strength (lb./N) Bundle Dia. (in./mm) Length (in./mm) Width (in./mm)  40/177.9 2.0/50.80 9/228.6 0.50/12.7 0.75/19.05  50/222.4 3.5/88.90 13/330.2 0.50/12.7 0.75/19.05  es  50/222.4 3.0/76.20 12/304.8 0.75/19.05  50/222.4 3.2/81.28 12/304.8 -  50/222.4 3.2/81.28 12/304.8 -  50/222.4 3.2/81.28 12/304.8 -  50/222.4 3.2/81.28 12/304.8 -  50/222.4 3.2/81.28 12/304.8 -  50/222.4 3.2/81.28 12/304.8 -

Black is standard colour.

Multiple colours available for identifying specific bundles \*Add — "FR" for UL94V-2 rated material, after colour choice. Contact your Regional Sales Office for availability and delivery.

## Two mounting bases designed for use with hook and loop fasteners



Cat. No.	Description	Screw Size	Max. Tie Width Accom.	Std. Pkg.		
Nylon 6/6 Mounting Bases						
TC368	2 in. x 2 in. Screw Mounted	π0	0.75/19.05	500		
TC368A	2 in. x 2 in. Adhesive Mounted	#8				

-40°F/-40°C to 176°F/80°C Natural nylon colour.

