





LM2N 3.5/90



Technical data	VDE	UL	CSA
Rated voltage (V)	125*	300	300
Rated current (A)	10	10	12
Wire size (mm ² /AWG)	1.5	22...14	28...14

*Pollution severity 3 / Overvoltage category III

Additional technical data see page 52

Solder pin length 3.2 mm 4.5 mm



Color

Poles	Type	Part No.	Part No.	Qty.
4	LM2N 3.5/4/90	1703700000	1720000000	100
6	LM2N 3.5/6/90	1703710000	1720010000	100
8	LM2N 3.5/8/90	1703720000	1720020000	50
10	LM2N 3.5/10/90	1703730000	1720030000	50
12	LM2N 3.5/12/90	1703740000	1720040000	50
14	LM2N 3.5/14/90	1703750000	1720050000	50
16	LM2N 3.5/16/90	1703760000	1720060000	50
18	LM2N 3.5/18/90	1703770000	1720070000	50
20	LM2N 3.5/20/90	1703780000	1720080000	50
22	LM2N 3.5/22/90	1703790000	1720090000	25
24	LM2N 3.5/24/90	1703800000	1720100000	25
26	LM2N 3.5/26/90	1703810000	1720110000	25
28	LM2N 3.5/28/90	1703820000	1720120000	25
30	LM2N 3.5/30/90	1703830000	1720130000	25
32	LM2N 3.5/32/90	1703840000	1720140000	25
34	LM2N 3.5/34/90	1703850000	1720150000	25
36	LM2N 3.5/36/90	1703860000	1720160000	25
38	LM2N 3.5/38/90	1703870000	1720170000	25
40	LM2N 3.5/40/90	1703880000	1720180000	25
42	LM2N 3.5/42/90	1703890000	1720190000	25
44	LM2N 3.5/44/90	1703900000	1720200000	25
46	LM2N 3.5/46/90	1703910000	1720210000	25
48	LM2N 3.5/48/90	1703920000	1720220000	25

Accessories	Page
Marking	42
Mounting	-
Screwdriver	45